All Nydree Engineered Flooring Products
Installation
Patterns Using 2 2/3” or 4” Wide
Fixed Length Double End Grooved Plank

Note: When a fixed length order is specified, Nydree Customer Service <u>requires</u> a drawing or diagram of the pattern lay-out. This information will allow production to verify that the flooring is milled correctly for the specified pattern. As with our standard flooring, it is important to install fixed length flooring directly from the polybag surrounding the cartons of flooring. If the flooring is allowed to acclimate for any length of time, humidity can alter the plank dimensions preventing the lay-up of the proposed pattern. It is good practice to ‘dry lay’ a few courses of the pattern to confirm a good lay-up. If there is any trouble whatsoever laying up the pattern, do not install the flooring, contact Nydree Flooring immediately @ 800.682.5698.



1115 Vista Park Drive ● Suites C&D ● Forest, VA 24551-0289 ● 800.682.5698 ● 434.525.5252 ● www.nydreeflooring.com

Standard Herringbone / Single Brick Patterns
Double End Grooved, Nydree Acrylic Infused Engineered Flooring can be used to make any standard herringbone or single brick pattern. The plank used for standard herringbone and single brick patterns must be ordered as one fixed length. This length is typically a multiple of the width, however any length from 14” to 46” may be specified for use in standard herringbone and single brick patterns. The most economical lengths for these patterns are 23” and 46”. (Keep in mind that there is an upcharge for fixed length plank.)

Certain patterns require the use of splines **(provided with the shipment when specified on order)** to “lock in” the floor and minimize overwood. The use of splines, when required, will provide sound, trouble-free installations.

If the direction of the tongue is alternated on adjacent rows and the ends of the previous row are locked in, no splines are needed for the basic herringbone pattern. See diagram below. No splines are required for single brick patterns.



Arrow indicates direction of the tongue.

Double Herringbone
Splines are required on double herringbone patterns where the edge is not locked in.

There are certain patterns that require a fixed length that is a multiple of the width.
The most economical sizes for these patterns are 2 2/3” x 21.28” and 4” x 20” (Keep in mind that there is an upcharge for fixed length plank.)

Basket Pattern, Double Brick or Triple Brick
Splines are required to lock in the ends.

Parquet Pattern (Cube)
Splines are required along the sides where groove side meets grooved ends.

See instructions in every carton for subfloor preparation, installation using Nydree Flooring MRA1585 adhesive, and maintenance procedures for Pedestrian 2.0 Finish.

© 2016 Nydree Flooring, LLC 03/16

1115 Vista Park Drive ● Suites C&D ● Forest, VA 24551-0289 ● 800.682.5698 ● 434.525.5252 ● www.nydreeflooring.com